PDR 908 ROP [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 8.0 kg in 52 min.



- Drum volume 130.00 l, load capacity 8.0 kg
- Tested for intensive use – unparalleled Miele quality
- Max. user convenience, full-touch colour display – M Touch Flex
- Precision drying of all fabrics – PerfectDry
- Future-proof networking via WiFi

EAN: 4002516871132 / Material number: 12752530 /
Old Material Number: 52908362GB

| Construction type and version | |
|---|---|
| Construction type | Front-loader, stackable |
| Range | Performance Plus |
| Front | Lotus white |
| Side panels | Powder-coated, lotus white |
| Fascia color | Stainless steel |
| Load in kg | 8.0 |
| Drum volume in l | 130.00 |
| Drying system | Exhaust air |
| Door opening [Ø] in mm | 370 |
| Door opening angle in degrees | 167 |
| Door hinge | left |
| Stainless steel honeycomb drum | Yes |
| **Application** | |
| Suitable for the hotel and catering industry | • |
| Suitable for retirement and care homes | • |
| Suitable for facility management | • |
| Suitable for launderettes | • |
| Suitable for residential homes and apartments | • |
| Suitable for dry cleaners | • |
| Suitable for commercial laundries | • |
| Suitable for small businesses | • |
| Suitable for universities, nurseries, and schools | • |
| Suitable for hospitals | • |
| Suitable for camp sites | • |
| Suitable for beauty salons, spas, and fitness centres | • |
| Suitable for doctors' and dentists' practices | • |
| Suitable for the petrochemicals industry | • |
| Suitable for the food-processing industry | • |
| Suitable for amusement parks & holiday complexes | • |
| **Performance data** | |
| Maximum evaporation capacity in l/hour | 4.8 |
| Specific energy consumption in kWh/kg | 0.50 |
| Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48 % in kW | 0.50 |
| Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture a | 0.42 |
| Programme duration in min. | 52 |
| Programme duration for Cottons/Normal drying programme with residual moisture at 48 % in minutes | 52 |
| Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40 % in | 47 |
| **Control system** | |
| Control system | M Touch Flex |
| Programmability | programmable |
| User interface | Residual moisture controlled |
| Max. delay start in h | 24 |
| Time left display | • |

Miele

# PDR 908 ROP [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 8.0 kg in 52 min.




EAN: 4002516871132 / Material number: 12752530 /
Old Material Number: 52908362GB

| | |
|---|---|
| Programme sequence indicator | • |
| Language can be selected easily at any time | • |
| **Standard electrical connection** | |
| Heating type | Electric |
| Electrical connection | 3N~ 400V 50/60HZ |
| Electric heater rating in kW | 5.22 |
| Total connected load in kW | 5.47 |
| Fuse rating in A | 13 |
| **Possible voltage variant 1** | |
| Electrical connection | 230V~ 50/60HZ |
| Heater rating in kW | 2.76 |
| Total connected load in kW | 2.99 |
| Fuse rating in A | 13 |
| **Dimensions and weight of dryer** | |
| External dimensions, height in mm | 850 |
| External dimensions, width in mm | 596 |
| External dimensions, depth in mm | 717 |
| External dimensions, gross height in mm | 940 |
| External dimensions, gross width in mm | 660 |
| External dimensions, gross depth in mm | 820 |
| Net weight in kg | 51.5 |
| Gross weight in kg | 57 |
| Maximum floor load in N | 920 |
| **Emissions data** | |
| Emission sound pressure level in the workplace | ≤70 dB(A) re 20 µPa |
| Heat dissipation into the room in MJ/h | 0.76 |
| **Features** | |
| Intelligent drum reversal | • |
| Axial airflow | • |
| Large-surface filter | • |
| PerfectDry | • |
| SoftLift drum ribs | • |
| Low temperature function | • |
| Communication slot | • |
| Drum lighting | • |
| Machine-independent accessories | • |
| **Efficiency** | |
| How it works | Vented |
| **Connection options** | |
| Payment system (optional) | • |
| Optical interface for service access | • |
| Peak-load negotiation / energy management (optional) | • |
| WiFi | • |
| LAN module (optional) | • |
| WiFiConn@ct | • |
| **Standards, test certificates and symbols** | |
| CE | • |
| VDE | • |

PDR 908 ROP [EL]

Professional vented dryer, Little Giants, electrically heated
with extremely short programme running times. Performance 8.0 kg in 52 min.




EAN: 4002516871132 / Material number: 12752530 /
Old Material Number: 52908362GB

| | |
|---|---|
| Splash-proof safety rating IPX4 | • |
| WEEE | • |
| UKCA | • |
| Complies with Machinery Directive 2006/42/EC | • |