Miele

PFD 104 SCVi XXL

Fully integrated XXL dishwasher with 3D MultiFlex cutlery tray

For large amounts of crockery in households, office tea rooms and utility areas.



- Wash performance: 14 place settings in just 20 min.*
- Maximum final rinse temperature of 82 °C
- 13 % less energy consumption**
- Everything completely dry – AutoOpen assisted drying
- Flexible loading of load items for the best cleaning results

* Programme running time without drying. The values quoted may vary depending on the on-site conditions (water inlet temperature/electrical connection).

** Based on the ECO programme, compared to predecessor.



EAN: 4002516446194 / Material number: 11808100 /
Old Material Number: 61010415GB

Construction type and version	
Construction type	Fully integrated dishwasher
XXL dishwashers	•
Range	ProfiLine
Wash system	Fresh water front loader
Number of levels	2
Front	Without front
Side panels	Galvanised
Fascia color	Obsidian black
Application	
Suitable for guesthouses	•
Suitable for universities and schools	•
Suitable for offices	•
Suitable for domestic use	•
Suitable for small businesses	•
Suitable for sports clubs	•
Performance data	
Tested virucidal efficacy	•
Proven hygiene	•
Circulation pump Qmax in l/min.	75
Shortest programme duration in min.	20
Maximum final rinse temperature in °C	82
Cleaning performance, place settings/cycle	14
Service life in wash cycles	12500
Miele MOVE	
Network-enabled with Miele MOVE	•
Control system	
Control system	Electronic controls
Programme selection	Programme selector buttons
Max. delay start in h	24
Time left display	•
Dishwashing programmes [number]	8
Adjustable final rinse temperature	•
Programme sequence indicator	•
Choice of display language	•
Check filter indicator	•
Standard electrical connection	
Electrical connection	AC 230V 50HZ
Heater rating in kW	6.10
Total connected load in kW	6.30
Fuse rating in A	32
Length of mains connection cable in m	1.70
Possible voltage variant 1	
Electrical connection	AC 230V 50HZ
Heater rating in kW	1.90
Total connected load in kW	2.10
Fuse rating in A	13

PFD 104 SCVi XXL

Fully integrated XXL dishwasher with 3D MultiFlex cutlery tray

For large amounts of crockery in households, office tea rooms and utility areas.



EAN: 4002516446194 / Material number: 11808100 /
Old Material Number: 61010415GB

Water connection/drainage	
Cold or hot water [number]	1
Required flow pressure in bar	1.00 - 10.00
Drain pump [DN]	22
Drain pump head height from floor level, max. in c	100
Integrated water softener	•
Maximum water hardness in mmol/l	6.50
Water protection system	Waterproof system
Length of water inlet hose in cm	150
Length of water drain hose in cm	150
Dimensions and weight	
External dimensions, height in mm	845
External dimensions, net width in mm	598
External dimensions, net depth in mm	550
External dimensions, gross height in mm	970
External dimensions, gross width in mm	670
External dimensions, gross depth in mm	690
Usable space in wash cabinet, height in mm	580
Usable space in wash cabinet, width in mm	510
Usable space in wash cabinet, depth of upper baske	450
Usable space in wash cabinet, depth of lower basket in mm	450
In-feed height above floor in mm	210
Required niche width in mm	600
Net weight [kg]	48
Gross weight in kg	57
Maximum floor load in N/m^2	1000
Emissions data	
Emissions – sound pressure at workplace	33 dB(A) re 20 µPa
Sound power (LwA) in dB(A) re 1 pW	45.0
Programmes	
Universal	•
Short	•
Hygiene	•
Cold/Pre-wash	•
Glasses	•
Plastics	•
Eco	•
Intensive	•
Basket design	
MaxiComfort P baskets	•
Flexible FlexLine basket design	•
FlexCare glass holder [number]	4
FlexCare cup rack [number]	2
Height-adjustable upper basket	•
Combinable with APFD 210 bottle basket	•
Patented 3D MultiFlex tray	•

PFD 104 SCVi XXL

Fully integrated XXL dishwasher with 3D MultiFlex cutlery tray

For large amounts of crockery in households, office tea rooms and utility areas.



EAN: 4002516446194 / Material number: 11808100 /
Old Material Number: 61010415GB

Features	
Drying	Active condensation drying, AutoOpen assisted drying, Extra drying
AutoClose	•
1 combi dispenser in the door for powder cleaning agent and rinsing agent	•
BrilliantLight	•
Knock2open	•
EcoFeedback	•
Brilliant GlassCare	•
Wash cabinet made from high-quality stai	•
Optical interface	•
SmartStart	•
FlexiTimer with EcoStart	•
Efficiency	
Load size of the ECO programme in place settings	14
Energy efficiency class (A–G)	E
Energy consumption of the ECO program per 100 cycles	95
Water consumption of the ECO programme per cycle in l	12.0
Acoustic airborne noise emission class (A–D)	C
Acoustic airborne noise emission in dB(A) re 1 pW	45
Programme running time of the ECO programme in min	250
Connection options	
External dispensing module for liquid cleaning agent	•
WiFi	•
Standards, test certificates and symbols	
CE	•
Complies with Machinery Directive 2006/42/EC	•
VDE	•
EMC radio suppressed	•
DIN EN 17735	•
EN 1717	•
Regulation 4 compliant	•
UKCA	•